

Kaindl FLOORS

Recommended tender specification

Dated: January 2021

1	Quality Floors. Made in Salzburg.	2
2	Environment and health – four reasons for Kaindl products	2
3	Laminate	3
3.1	Classic Touch	3
3.1.1	7.0 Standard plank	3
3.1.2	8.0 Standard plank	3
3.1.3	8.0 Wide plank	4
3.1.4	8.0 Premium plank	4
3.2	Natural Touch	5
3.2.1	8.0 Standard plank	5
3.2.2	8.0 Wide plank	5
3.2.3	10.0 Long plank	6
3.2.4	10.0 Premium plank	6
3.3	Easy Touch	7
3.3.1	8.0 Premium plank	7
4	AQUA PRO	8
4.1	Supreme Easy Touch	8
4.1.1	8.0 Premium plank	8
4.2	Select Classic Touch	8
4.2.1	8.0 Standard plank	8
4.2.2	8.0 Smart plank	9
4.3	Select Natural Touch	9
4.3.1	8.0 Standard plank	9
4.3.2	8.0 Tile	10
4.3.3	12.0 Standard plank	10
4.4	Supreme Natural Touch	11
4.4.1	12.0 Standard plank	11
4.5	Wood Veneer Parquet	12
4.5.1	8.5 Wide plank	12
5	Vinyl	13
5.1	Solid	13
5.1.1	8.0 Medium plank	13
5.2	Solid pro	13
5.2.1	4.0 Compact plank	13
5.2.2	5.0 Compact plank	14
5.2.3	5.0 Compact tile	14

1 Quality Floors. Made in Salzburg.

The name Kaindl stands for floorings that are high quality, robust and vivid. In our collection, you will find floorings made regionally in Austria that model themselves on nature and new designs that have the potential to become trendsetters. With a large number of surfaces and all kinds of different plank sizes, there is something suitable for every area of use.

AQUA PRO

Anything but afraid of water. With the AQUA PRO technology, Kaindl has developed a completely new generation of water-resistant floorings. Choose from a wide range of diverse decors with authentic wood look and feel in the AQUA PRO Supreme & Select product categories or discover floorings with a wooden surface and intelligent moisture protection. The special feature of these durable floorings is their moisture-resistant organic AQUAtec substrate and a special, self-closing tongue-and-groove profile in combination with a moisture-repelling edge seal.

AQUA PRO Wood

Real wood flair with moisture protection. Kaindl wood floorings are luxurious, cosy and natural. The high-quality brushed Oak surface lends any room homely flair. The innovative feature is the intelligent moisture protection. This makes the real wood surface of the floor well protected, even for the worst-case scenario.

Laminate

Robust and authentic. Kaindl laminate floorings are in no way inferior to a “real” wooden floor. Whether floorings from the “Classic Touch”, “Natural Touch” or “Easy Touch” product group: Discover unusual decors, tangibly authentic surfaces and a large number of decorative patterns.

Vinyl

Trendy and robust. At first glance, it is difficult to tell the difference between the razor-sharp wood decors of these vinyl floorings and a real wood plank. The particular feature is their robustness. Not only SOLID, but also SOLID PRO floorings are resistant to wetness, dirt and scratches. Thanks to their lay-up and pleasant surface, excellent underfoot comfort is guaranteed.

2 Environment and health – four reasons for Kaindl products

The circular economy

For us, wood is an important raw material that we handle responsibly. We therefore use recycled wood in our production, thereby giving it a second life.

Kaindl products can naturally be recycled at the end of their life cycle.

Ecological

90 % of the material used to make Kaindl floorings is the renewable raw material wood from our regional wood industry. Each second, one cubic metre of it grows in Austria’s forests. Sustainable forest management ensures that more wood grows than is removed.

Low emission products

Our products are CO₂-neutral. Thanks to their high wood content, they have an unbeatable life cycle assessment, and actively contribute to climate protection. One pallet of KAINDL flooring binds 1.4 t of CO₂. This is equal to the emissions of a car trip of around 7,000 kilometres.

Healthy living

Anyone who buys Kaindl floorings, buys a healthy living environment! Our products meet international standards, they are free from harmful plasticisers and pollutants and ensure high-quality room air. We guarantee it!

3 Laminate

3.1 Classic Touch

3.1.1 7.0 Standard plank

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, hotel rooms and small offices)

Description

Laminate flooring with use class 31/AC3 to EN 13329, formaldehyde emission E1

- Low-swelling HDF substrate, in conformity with CARB Phase II and EPA TSCA Title VI
- Facing made of resistant/abrasion-resistant overlay, decor paper and backing paper
- Glue-free, convenient laying system, Kaindl Loc: Angle/Angle
- Thermal resistance 0.069 m² K/W to ISO 8302
- Reaction to fire Cfl-S1, to EN 13501-1
- Certificates: GREENGUARD, PEFC

Decors Visit <https://www.kaindl.com>

Guarantee

15 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1383 x 193 x 7 mm
 Decor and texture: _____
 Alternative product: _____
 Laying _____ € / m²
 Final cleaning _____ €

3.1.2 8.0 Standard plank

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, offices, and sales rooms)

Description

Laminate flooring with use class 32/AC4 to EN 13329, formaldehyde emission E1

- Optima HDF substrate, in conformity with CARB Phase II and EPA TSCA Title VI
- Facing made of resistant/abrasion-resistant overlay, decor paper and backing paper
- Glue-free, convenient laying system, Kaindl Loc: Fold Down
- Thermal resistance 0.078 m² K/W to ISO 8302
- Reaction to fire Cfl-S1, to EN 13501-1
- Certificates: GREENGUARD GOLD, PEFC

Decors Visit <https://www.kaindl.com>

Guarantee

30 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1383 x 193 x 8 mm
 Decor and texture: _____
 Alternative product: _____
 Laying _____ € / m²
 Final cleaning _____ €

3.1.3 8.0 Wide plank

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, offices and sales rooms)

Description

Laminate flooring with use class 32/AC4 to EN 13329, formaldehyde emission E1

- Optima HDF substrate, in conformity with CARB Phase II and EPA TSCA Title VI
- Facing made of resistant/abrasion-resistant overlay, decor paper and backing paper
- Glue-free, convenient laying system, Kaindl Loc: Fold Down
- Thermal resistance 0.078 m² K/W to ISO 8302
- Reaction to fire Cfl-S1, to EN 13501-1
- Certificates: GREENGUARD GOLD, PEFC

Decors Visit <https://www.kaindl.com>

Guarantee

30 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1383 x 244 x 8 mm
 Decor and texture: _____
 Alternative product: _____
 Laying _____ € / m²
 Final cleaning _____ €

3.1.4 8.0 Premium plank

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, offices and sales rooms)

Description

Laminate flooring with use class 32/AC4 to EN 13329, formaldehyde emission E1

- Optima HDF substrate, in conformity with CARB Phase II and EPA TSCA Title VI
- Facing made of resistant/abrasion-resistant overlay, decor paper and backing paper
- Glue-free, convenient laying system, Kaindl Loc: Fold Down
- Thermal resistance 0.078 m² K/W to ISO 8302
- Reaction to fire Cfl-S1, to EN 13501-1
- Certificates: GREENGUARD GOLD, PEFC

Decors Visit <https://www.kaindl.com>

Guarantee

30 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1383 x 159 x 8 mm
 Decor and texture: _____
 Alternative product: _____
 Laying _____ € / m²
 Final cleaning _____ €

3.2 Natural Touch

3.2.1 8.0 Standard plank

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, offices and sales rooms)

Description

Laminate flooring with use class 32/AC4 to EN 13329, formaldehyde emission E1

- Optima HDF substrate, in conformity with CARB Phase II and EPA TSCA Title VI
- Facing made of resistant/abrasion-resistant overlay, decor paper and backing paper
- Glue-free, convenient laying system, Kaindl Loc: Fold Down
- Thermal resistance 0.078 m² K/W to ISO 8302
- Reaction to fire Cfl-S1, to EN 13501-1
- Certificates: GREENGUARD GOLD, PEFC

Decors Visit <https://www.kaindl.com>

Guarantee

30 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1383 x 193 x 8 mm
 Decor and texture: _____
 Alternative product: _____
 Laying _____ € / m²
 Final cleaning _____ €

3.2.2 8.0 Wide plank

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, offices and sales rooms)

Description

Laminate flooring with use class 32/AC4 to EN 13329, formaldehyde emission E1

- Optima HDF substrate, in conformity with CARB Phase II and EPA TSCA Title VI
- Facing made of resistant/abrasion-resistant overlay, decor paper and backing paper
- Glue-free, convenient laying system, Kaindl Loc: Fold Down
- Thermal resistance 0.078 m² K/W to ISO 8302
- Reaction to fire Cfl-S1, to EN 13501-1
- Certificates: GREENGUARD GOLD, PEFC

Decors Visit <https://www.kaindl.com>

Guarantee

30 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1383 x 244 x 8 mm
 Decor and texture: _____
 Alternative product: _____
 Laying _____ € / m²
 Final cleaning _____ €

3.2.3 10.0 Long plank

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, offices and sales rooms)

Description

Laminate flooring with use class 32/AC4 to EN 13329, formaldehyde emission E1

- Optima HDF substrate, in conformity with CARB Phase II and EPA TSCA Title VI
- Facing made of resistant/abrasion-resistant overlay, decor paper and backing paper
- Glue-free, convenient laying system, Kaindl Loc: Fold Down
- Thermal resistance 0.093 m² K/W to ISO 8302
- Reaction to fire Cfl-S1, to EN 13501-1
- PEFC certificate

Decors Visit <https://www.kaindl.com>

Guarantee

30 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 2000 x 192 x 10 mm
 Decor and texture: _____
 Alternative product: _____
 Laying _____ € / m²
 Final cleaning _____ €

3.2.4 10.0 Premium plank

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, offices and sales rooms)

Description

Laminate flooring with use class 32/AC4 to EN 13329, formaldehyde emission E1

- Optima HDF substrate, in conformity with CARB Phase II and EPA TSCA Title VI
- Facing made of resistant/abrasion-resistant overlay, decor paper and backing paper
- Glue-free, convenient laying system, Kaindl Loc: Fold Down
- Thermal resistance 0.093 m² K/W to ISO 8302
- Reaction to fire Cfl-S1, to EN 13501-1
- Certificates: GREENGUARD GOLD, PEFC

Decors Visit <https://www.kaindl.com>

Guarantee

30 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1383 x 159 x 10 mm
 Decor and texture: _____
 Alternative product: _____
 Laying _____ € / m²
 Final cleaning _____ €

3.3 Easy Touch

3.3.1 8.0 Premium plank

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, offices and sales rooms)

Description

Laminate floorings with directly applied printing, use class 32/AC4 to EN 15468, formaldehyde emission E1

- Optima HDF substrate, in conformity with CARB Phase II and EPA TSCA Title VI
- Coating made of multi-layer UV varnish, digital printing and varnish backing
- Glue-free, convenient laying system, Kaindl Loc: Fold Down
- Thermal resistance 0.078 m² K/W to ISO 8302
- Reaction to fire Cfl-S1, to EN 13501-1
- Certificates: GREENGUARD GOLD, PEFC

Decors Visit <https://www.kaindl.com>

Guarantee

30 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1383 x 159 x 8 mm

Decor and texture: _____

Alternative product: _____

Laying _____ € / m²

Final cleaning _____ €

4 AQUA PRO

4.1 Supreme Easy Touch

4.1.1 8.0 Premium plank

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, offices and sales rooms)

Description

Water-resistant laminate flooring with use class 32/AC4 to EN 13329, formaldehyde emission E1

- Aquatec moisture resistant, organic substrate, PVC free, in conformity with CARB Phase II and EPA TSCA Title VI
- Facing made of resistant/abrasion-resistant overlay, decor paper and backing paper
- Glue-free, convenient laying system, Kaindl Loc: Angle/Tap
- Soft bevel finish with edge seal
- Thermal resistance 0.078 m² K/W to ISO 8302
- Reaction to fire Cfl-S1, to EN 13501-1
- Certificates: GREENGUARD GOLD, PEFC

Decors Visit <https://www.kaindl.com>

Guarantee

30 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1383 x 159 x 8 mm
 Decor and texture: _____
 Alternative product: _____
 Laying _____ € / m²
 Final cleaning _____ €

4.2 Select Classic Touch

4.2.1 8.0 Standard plank

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, offices and sales rooms)

Description

Water-resistant laminate flooring with use class 33/AC4 to EN 13329, formaldehyde emission E1

- Aquatec moisture resistant, organic substrate, PVC free, in conformity with CARB Phase II and EPA TSCA Title VI
- Facing made of resistant/abrasion-resistant overlay, decor paper and backing paper
- Glue-free, convenient laying system, Kaindl Loc: Angle/Tap
- Aqua Protect bevel finish with edge seal
- Thermal resistance 0.078 m² K/W to ISO 8302
- Reaction to fire Cfl-S1, to EN 13501-1
- Certificates: GREENGUARD GOLD, PEFC

Decors Visit <https://www.kaindl.com>

Guarantee

30 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1383 x 193 x 8 mm
 Decor and texture: _____
 Alternative product: _____
 Laying _____ € / m²
 Final cleaning _____ €

4.2.2 8.0 Smart plank

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, offices and sales rooms)

Description

Water-resistant laminate flooring with use class 33/AC4 to EN 13329, formaldehyde emission E1

- Aquatec moisture resistant, organic substrate, PVC free, in conformity with CARB Phase II and EPA TSCA Title VI
- Facing made of resistant/abrasion-resistant overlay, decor paper and backing paper
- Glue-free, convenient laying system, Kaindl Loc: Angle/Tap
- Aqua Protect bevel finish with edge seal
- Thermal resistance 0.093 m² K/W to ISO 8302
- Reaction to fire Cfl-S1, to EN 13501-1
- Certificates: GREENGUARD GOLD, PEFC

Decors Visit <https://www.kaindl.com>

Guarantee

30 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1290 x 329 x 8 mm
 Decor and texture: _____
 Alternative product: _____
 Laying _____ € / m²
 Final cleaning _____ €

4.3 Select Natural Touch

4.3.1 8.0 Standard plank

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, offices and sales rooms)

Description

Water-resistant laminate flooring with use class 33/AC4 to EN 13329, formaldehyde emission E1

- Aquatec moisture resistant, organic substrate, PVC free, in conformity with CARB Phase II and EPA TSCA Title VI
- Facing made of resistant/abrasion-resistant overlay, decor paper and backing paper
- Glue-free, convenient laying system, Kaindl Loc: Angle/Tap
- Aqua Protect bevel finish with edge seal
- Thermal resistance 0.093 m² K/W to ISO 8302
- Reaction to fire Cfl-S1, to EN 13501-1
- Certificates: GREENGUARD GOLD, PEFC

Decors Visit <https://www.kaindl.com>

Guarantee

30 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1383 x 193 x 8 mm
 Decor and texture: _____
 Alternative product: _____
 Laying _____ € / m²
 Final cleaning _____ €

4.3.2 8.0 Tile

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, offices and sales rooms)

Description

Water-resistant laminate flooring with use class 33/AC4 to EN 13329, formaldehyde emission E1

- Aquatec moisture resistant, organic substrate, PVC free, in conformity with CARB Phase II and EPA TSCA Title VI
- Facing made of resistant/abrasion-resistant overlay, decor paper and backing paper
- Glue-free, convenient laying system, Kaindl Loc: Angle/Tap
- Aqua Protect bevel finish with edge seal
- Thermal resistance 0.093 m² K/W to ISO 8302
- Reaction to fire Cfl-S1, to EN 13501-1
- Certificates: GREENGUARD GOLD, PEFC

Decors Visit <https://www.kaindl.com>

Guarantee

30 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1290 x 329 x 8 mm
 Decor and texture: _____
 Alternative product: _____
 Laying _____ € / m²
 Final cleaning _____ €

4.3.3 12.0 Standard plank

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, offices and sales rooms)

Description

Water-resistant laminate flooring with use class 33/AC4 to EN 13329, formaldehyde emission E1

- Aquatec moisture resistant, organic substrate, PVC free, in conformity with CARB Phase II and EPA TSCA Title VI
- Facing made of resistant/abrasion-resistant overlay, decor paper and backing paper
- Glue-free, convenient laying system, Kaindl Loc: Angle/Tap
- Aqua Protect bevel finish with edge seal
- Thermal resistance 0.093 m² K/W to ISO 8302
- Reaction to fire Cfl-S1, to EN 13501-1
- Certificates: GREENGUARD GOLD, PEFC

Decors Visit <https://www.kaindl.com>

Guarantee

30 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1383 x 193 x 12 mm
 Decor and texture: _____
 Alternative product: _____
 Laying _____ € / m²
 Final cleaning _____ €

4.4 Supreme Natural Touch

4.4.1 12.0 Standard plank

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, offices and sales rooms)

Description

Water-resistant laminate flooring with use class 33/AC4 to EN 13329, formaldehyde emission E1

- Aquatec moisture resistant, organic substrate, PVC free, in conformity with CARB Phase II and EPA TSCA Title VI
- Facing made of resistant/abrasion-resistant overlay, decor paper and backing paper
- Glue-free, convenient laying system, Kaindl Loc: Angle/Tap
- Pressed bevel finish with edge seal
- Thermal resistance 0.093 m² K/W to ISO 8302
- Reaction to fire Cfl-S1, to EN 13501-1
- Certificates: GREENGUARD GOLD, PEFC

Decors Visit <https://www.kaindl.com>

Guarantee

35 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1290 x 193 x 12 mm
 Decor and texture: _____
 Alternative product: _____
 Laying _____ € / m²
 Final cleaning _____ €

4.5 Wood Veneer Parquet

4.5.1 8.5 Wide plank

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, offices and sales rooms)

Description

Water-resistant wooden flooring with use class 32/AC4 to EN 13329, formaldehyde emission E1

- Aquatec moisture resistant, organic substrate, PVC free, in conformity with CARB Phase II and EPA TSCA Title VI
- Wood veneer surface made of multi-layer, abrasion-resistant UV lacquer and wood veneer backing
- Glue-free, convenient laying system, Kaindl Loc: Angle/Tap
- Soft bevel finish with edge seal
- Thermal resistance 0.078 m² K/W to ISO 8302
- Reaction to fire Dfl-S1, to EN 13501-1
- Certificates: GREENGUARD GOLD, PEFC

Decors Visit <https://www.kaindl.com>

Guarantee

20 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1383 x 244 x 8,5 mm

Decor and texture: _____

Alternative product: _____

Laying _____ € / m²

Final cleaning _____ €

5 Vinyl

5.1 Solid

5.1.1 8.0 Medium plank

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, offices and sales rooms)

Description

Vinyl flooring, use class 32 to EN 16511

- Low-swelling HDF substrate, in conformity with CARB Phase II and EPA TSCA Title VI
- Resistant, resilient vinyl layer with decor film
- Glue-free, convenient laying system, Kaindl Loc: Fold Down
- Thermal resistance 0.1088 m² K/W to ISO 8302
- Reaction to fire Bfl-S1, to EN 13501-1

Decors Visit <https://www.kaindl.com>

Guarantee

30 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1383 x 223 x 8 mm
 Decor and texture: _____
 Alternative product: _____
 Laying _____ € / m²
 Final cleaning _____ €

5.2 Solid pro

5.2.1 4.0 Compact plank

Areas of application

For laying as floating flooring, for internal use in dry conditions (domestic living areas, offices and sales rooms)

Description

Mineral vinyl flooring, use class 32 to EN 16511

- SPC mineral vinyl substrate with resistant UV lacquer surface, digitally printed
- Glue-free, convenient laying system, Kaindl Loc: Fold Down
- Thermal resistance 0.437 m² K/W to EN 12667
- Reaction to fire Bfl-S1, to EN 13501-1

Decors Visit <https://www.kaindl.com>

Guarantee

25 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1210x 192 x 4 mm
 Decor and texture: _____
 Alternative product: _____
 Laying _____ € / m²
 Final cleaning _____ €

5.2.2 5.0 Compact plank

Areas of application

For laying as floating flooring, for internal use in dry conditions (open plan offices, department stores, multi-purpose hall-type buildings and main halls in railway stations)

Description

Mineral vinyl flooring, use class 34 to EN 16511

- Mineral vinyl substrate with resistant UV lacquer surface, digitally printed
- Glue-free, convenient laying system, Kaindl Loc: Fold Down
- Thermal resistance 0.437 m² K/W to EN 12667
- Reaction to fire Bfl-S1, to EN 13501-1

Decors Visit <https://www.kaindl.com>

Guarantee

30 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 1210 x 192 x 5 mm

Decor and texture: _____

Alternative product: _____

Laying _____ € / m²

Final cleaning _____ €

5.2.3 5.0 Compact tile

Areas of application

For laying as floating flooring, for internal use in dry conditions (open plan offices, department stores, multi-purpose hall-type buildings and main halls in railway stations)

Description

Mineral vinyl flooring, use class 34 to EN 16511

- Mineral vinyl substrate with resistant UV lacquer surface, digitally printed
- Glue-free, convenient laying system, Kaindl Loc: Fold Down
- Thermal resistance 0.437 m² K/W to EN 12667
- Reaction to fire Bfl-S1, to EN 13501-1

Decors Visit <https://www.kaindl.com>

Guarantee

30 years in accordance with the Kaindl guarantee conditions

Product requirement

Dimensions: 600 x 295 x 5 mm

Decor and texture: _____

Alternative product: _____

Laying _____ € / m²

Final cleaning _____ €