

T E S T C E R T I F I C A T E

PT-20-08-27-06

- Product:** Kaindl Decor Fiberboard MDF/CA
Melamine faced boards for interior use
acc. to DIN EN 14322:2017-07
- Client:** M. KAINDL OG, Kaindlstrasse 2, 5071 Wals/Salzburg, Austria
- Order:** Testing of formaldehyde emission acc. to DIN EN 16516, DIN EN ISO 12460-5,
DIN EN ISO 12460-3 and ASTM D6007-14
- Basis:** Test Report No. 2118037/2020/CT/1 of 28 April 2020
Test Report No. 2117197/2020/02-MDF of 9 Jun 2019


Test Result:

Characteristic	Requirement
Formaldehyde emission acc. to EN 16516 (ChemVerbotsV)	≤ 0,1 ppm
Formaldehyde emission acc. to ISO 12460-5 (EN 13986)	≤ 8 mg/100 g atro
Formaldehyde emission acc. to ISO 12460-3	≤ 3,5 mg/m ² h
Formaldehyde emission raw board acc. to ASTM D6007-14	≤ 0,11 ppm

Kaindl Decor Fiberboards MDF/CA are subject to a contractually specified inspection of the production and on laboratory and comparative tests.
The formaldehyde emission is below the max. permissible requirement acc. to the German Chemicals Prohibition Ordinance (ChemVerbotsV), valid from 1 Jan 2020. The products fulfill the requirement to Class E1 acc. to EN 13986.
The formaldehyde concentration of the raw board acc. to ASTM D6007-14 is below the the maximum permissible requirement of EPA/CARB.

Validity: 31 Dec 2020

Dresden, 27 August 2020



Head of laboratory




Engineer in charge