

T E S T C E R T I F I C A T E

PT-20-06-05-15

Product: Kaindl Bonded Board P2/CA
 CPL coated boards for interior use under dry conditions
 Continuously pressured laminates (CPL) acc. to DIN EN 438-3:2016-06 of
 Types "Kaindl Counter Top", "Kaindl Forming Element", "Kaindl Bonded Board"
 and "Kaindl Laminated Board"
 Raw board: Kaindl Particleboard P2/CA

Client: M. KAINDL OG, Kaindlstrasse 2, 5071 Wals/Salzburg, Austria

Order: Testing of formaldehyde emission acc. to DIN EN 16516, DIN EN ISO 12460-5,
 DIN EN ISO 12460-3 and ASTM D6007-14

Basis: Test Report No. 2514579/2019/2/W of 27 Nov 2019
 Test Report No. 2118037-W-P2/E1-CPL-2018 of 8 May 2019
 Test Report No. 2117197/2019/04-PB of 21 Nov 2019

Test Result:

Characteristic	Requirement
Formaldehyde emission acc. to EN 16516 (ChemVerbotsV)	≤ 0,1 ppm
Formaldehyde emission acc. to ISO 12460-5 (EN 13986)	≤ 8 mg/100 g atro
Formaldehyde emission acc. to ISO 12460-3	≤ 3,5 mg/m ² h
Formaldehyde emission raw board acc. to ASTM D6007-14	≤ 0,09 ppm

Kaindl Bonded Boards P2/CA are subject to a contractually specified inspection of the production and on laboratory and comparative tests.
 The formaldehyde emission is below the max. permissible requirement acc. to the German Chemicals Prohibition Ordinance (ChemVerbotsV), valid from 1 Jan 2020.
 The products fulfill the requirement to Class E1 acc. to EN 13986.
 The formaldehyde concentration of the raw particle board acc. to ASTM D6007-14 is below the the maximum permissible requirement of EPA/CARB.

Validity: 31 Dec 2020

Dresden, 5 June 2020

i.v. W. W. W.
 Head of laboratory



lid

Engineer in charge