

T E S T C E R T I F I C A T E

PT-22-02-02-10

- Product:** Kaindl Veneered Fiber Board MDF/CA
Veneered boards for interior use
acc. to EN 14322:2017, Thickness range: > 12 mm to 19 mm
- Client:** M. KAINDL GmbH, Kaindlstrasse 2, 5071 Wals/Salzburg, Austria
- Order:** Determination of mechanical and chemical properties
- Basis:** Test Report No. 2118037-W-MDF/CA-12/19-2021 of 15 Dec 2021
Test Report No. 2118037-W-MDF/CA-FUR-2021 of 2 Feb 2022
Test Report No. 2118037-W-P2/CA-FUR-2021 of 2 Feb 2022
Test Report No. 2117197/2021/03-MDF of 25 Aug 2021
Test Report No. 2118037/2021/CT/5 of 2 Jun 2021

Test Result:

Characteristic	Requirement
Bending strength acc. to EN 310	≥ 20 N/mm ²
Modulus of elasticity acc. to EN 310	≥ 2200 N/mm ²
Thickness swelling acc. to EN 317	≤ 12 %
Internal bond strength acc. to EN 319	≥ 0,55 N/mm ²
Surface soundness acc. to EN 311	≥ 0,80 N/mm ²
HCHO emission raw board acc. to ASTM D6007-14	≤ 0,11 ppm
HCHO emission acc. to EN 16516 (ChemVerbotsV)	≤ 0,1 ppm
PCP content acc. to CEN/TR 14823	≤ 3 ppm
Lindan content acc. to CEN/TR 14823	≤ 1 ppm
Migration of heavy metals acc. to EN 71-3	Category III

Based on a contractually specified inspection of the production and on laboratory tests, it can be stated that the tested fiber boards fulfill the requirements of Type MDF acc. to EN 622-5 and acc. to EN 14322.

The formaldehyde emission is below the maximum permissible requirement acc. to the German Chemicals Prohibition Ordinance (ChemVerbotsV), valid from 1 Jan 2020.

The formaldehyde concentration acc. to ASTM D6007-14 is below the the maximum permissible requirement of EPA/CARB/TSCA.

Validity: 31 Dec 2022

Dresden, 2 February 2022



Head of laboratory




Engineer in charge