

T E S T C E R T I F I C A T E

PT-21-12-21-15

- Product:** Kaindl Veneered MDF/CA
Veneered boards for interior use
acc. to EN 14322:2017
- Client:** M. KAINDL GmbH, Kaindlstrasse 2, 5071 Wals/Salzburg, Austria
- Order:** Testing of formaldehyde emission acc. to EN 16516, EN ISO 12460-5,
EN ISO 12460-3 and ASTM D6007-14
- Basis:** Test Report No. 2118037/2021/CT/6 of 2 Jul 2021
Test Report No. 2118037/2021/CT/5 of 2 Jun 2021
Test Report No. 2118037/2021/CT/9 of 10 Nov 2021
Test Report No. 2117197/2021/03-MDF of 25 Aug 2021

Test Result:

Characteristic	Requirement
Formaldehyde emission acc. to EN 16516 (ChemVerbotsV)	≤ 0,1 ppm
Formaldehyde emission acc. to ISO 12460-5 (EN 13986)	≤ 8 mg/100 g atro
Formaldehyde emission acc. to ISO 12460-3	≤ 3,5 mg/m ² h
Formaldehyde emission raw board acc. to ASTM D6007-14	≤ 0,11 ppm

Kaindl Veneered MDF/CA are subject to a contractually specified inspection of the production and on laboratory and comparative tests.
The formaldehyde emission is below the max. permissible requirement acc. to the German Chemicals Prohibition Ordinance (ChemVerbotsV), valid from 1 Jan 2020. The products fulfill the requirement to Class E1 acc. to EN 13986.
The formaldehyde concentration of the raw board acc. to ASTM D6007-14 is below the the maximum permissible requirement of EPA/CARB/TSCA.

Validity: 31 Dec 2022

Dresden, 21 December 2021



Head of laboratory




Engineer in charge