

T E S T C E R T I F I C A T E

ST-26-02-17-01

Product: Laminate floor covering of assembly group 70.1: Kaindl FLOORganic XPT supreme Natural Touch 12.5 mm
Client: Kaindl Flooring GmbH, Kaindlstrasse 2, 5071 Wals/ Salzburg, Austria
Order: Carry out of an external quality control on laminate floor coverings according to EN 13329:2023, ISO 14486:2025 and on other selected properties
Test reports: 2117129/2025/2, 5/5W/5W1/8-10, 12, 15 and quarterly reports of CARB/EPA surveillance
Test results:

| Properties | Results of classification requirements tests according to EN 13329:2023 / ISO 14486:2025 / other tests | |
|---|--|-----------|
| Abrasion resistance | AC5 | |
| Impact resistance | Small ball | ≥ 70 mm |
| | Big ball | ≥ 1000 mm |
| Resistance against staining | Groups 1 und 2 | Grade 5 |
| | Group 3 | Grade 4 |
| Effect of a furniture leg | no visible damages | |
| Effect of a castor chair | no visible damages | |
| Thickness swelling | ≤ 10 % | |
| ISO 4760 and NALFA surface swell test | < 0,3 mm and Grad 2 / no water leak through the joints | |
| Locking strength | f _{10,2} ≥ 1 kN/m / f _{s0,2} ≥ 2 kN/m | |
| Surface soundness | ≥ 1,25 N/mm ² | |
| PCP/Lindane | < 5 ppm | |
| Formaldehyde release according to EN ISO 12460-3 | Austrian formaldehyde ordinance is fulfilled | |
| Formaldehyde emission according to EN 717-1 | Requirements FA-REACH-2026 ¹ / ChemVerbotsV-2020 ² fulfilled | |
| Formaldehyde requirements of CARB Phase 2 and EPA TSCA Title VI | Carrier boards certified by TPC 10 | |
| Migration of heavy metals, chromium VI and organostannic compounds according to EN 71-3 | Requirements fulfilled | |
| VOC-Emission according to EN 16516 | Requirements of AgBB-scheme and MVVTB ABG annex 8, French Class A+, BREEAM General Level; Belgian VOC regulation; Finnish M1 classification, LEED v4, and TÜV PROFICERT-product Interior PREMIUM are fulfilled | |

¹ Formaldehyde emission limit value according to COMMISSION REGULATION (EU) 2023/1464 of 14 July 2023 amending Annex XVII to Regulation (EC) No 1907/2006 of the European Parliament and of the Council as regards formaldehyde and formaldehyde releasers, Formaldehyde limit value 0.062 mg/m³ for furniture and wood-based products.

² Limit value for formaldehyde emissions in accordance with the Chemicals Prohibition Ordinance (ChemVerbotsV) Annex 1 to §3 of 20.01.2017 in conjunction with the announcement of analytical methods published on November 26, 2018, BAnz AI 26.11.2018 B2, 124 µg/m³ (0.1 ppm)


The tested laminate floor covering meets all requirements according to EN 13329:2023 and ISO 14468:2025 for the class 33.

This test certificate is valid until 16/02/2027.

Dresden, 17/02/2026



Head of laboratory

Engineer in charge