**REPAIR SET – INSTRUCTIONS FOR USE** 

Individual Repair Set to mend slight damages (splits in the surface, scratches, open joints). The desired colour is obtained by mixing the pigments with the basic paste.

## Instructions

- For most effective adhesion, make sure that the area is clean and free of oil, wax or grease. You may need to use a chisel to remove any loose pieces attached to the surface.
- Tape around the edges of the damaged area with adhesive tape.
- Available REPAIR KITS:

Repair Set	Possible colour combinations
No. 2	medium to dark designs
No. 3	light to medium designs

• Find the best colour match for your product on the back of the package insert.

Using the colour strip, select the colour that best matches the design of the damaged surface. The mixing ratio for the lightest and darkest colour shades is specified on the colour strip. Adjust the mixing ratio until it appears to match the colour shade of the floor. Mix the basic paste (large tube) with the colour pigment to produce a uniform mixture. You can adjust the colour hue by adding more pigment one drop at a time. We recommend that you use only one drop per colour correction.

## Before using pigment, please shake well.

## Once mixed, the paste must be used within a few minutes.

• Position a scraper at the edge of the damaged area. Press the scraper with the paste firmly onto the surface while slowly dragging it across the damaged area. This will ensure that the damaged area is evenly filled with the Repair Set.

In the case of deeper damage, you will need to apply several layers of the Repair Set. You can apply as many layers as necessary to even it up with the surface. Let the paste dry for about 10 minutes between applications of individual layers.

Depending on the depth of the damage, the paste may shrink during the hardening process and require followup processing.

- Using a clean scraper, remove excess paste from the damaged area. Before the paste hardens, wipe away any messy spots with a damp cloth. Hardened Repair Set residue is easily removed with acetone. Use the acetone sparingly, however, or you might remove too much paste or start to dissolve the paste you applied.
- Allow repaired areas to harden for at least 1 hour before using.

## **General information**

- The Repair Set is not affected by household products such as detergents.
- The Repair Set does not adhere to the uppermost surface, but binds itself with the base papers and core board.
- The Repair Set is the ideal solution for repairing laminate flooring.
- Because the Repair Set begins to harden as soon as it comes into contact with oxygen, always close the tube immediately after use.
- Keep the Repair Set safe from freezing temperatures and out of the reach of children.
- The basic paste and pigments are water-based and solvent-free.